

Lecture 3

- Review
- Blocks and Compound Statements
- Control Flow
 - Conditional Statements
 - Loops
- Functions
- Modular Programming
- Variable Scope
 - Static Variables
 - Register Variables

Review: Definitions

- Variable -name/reference to a stored value (usually in memory)
- Data type -determines the size of a variable in memory, what values it can take on, what operations are allowed
- Operator -an operation performed using 1-3 variables
- Expression -combination of literal values/variables and operators/functions

Review: Data types

- Various sizes (**char**, **short**, **long**, **float**, **double**)
- Numeric types - **signed/unsigned**
- Implementation -little or big endian
- Careful mixing and converting (casting) types

Review: Operators

- Unary, binary, ternary (1-3 arguments)
- Arithmetic operators, relational operators, binary (bitwise and logical) operators, assignment operators, etc.
- Conditional expressions
- Order of evaluation (precedence, direction)

Lecture 3

- Review
- **Blocks and Compound Statements**
- Control Flow
 - Conditional Statements
 - Loops
- Functions
- Modular Programming
- Variable Scope
 - Static Variables
 - Register Variables

Blocks and compound statements

- A simple statement ends in a semicolon:

```
z = foo(x+y);
```

- Consider the multiple statements:

```
temp = x+y;
```

```
z = foo(temp);
```

- Curly braces – combine into compound statement/*block*

Blocks

- Block can substitute for simple statement
- Compiled as a single unit
- Variables can be declared inside

```
{  
    int temp = x+y;  
    z = foo(temp);  
}
```

- Block can be empty { }
- No semicolon at end

Nested blocks

- Blocks nested inside each other

```
{  
  int temp = x+y;  
  z = foo(temp);  
  {  
    float temp2 = x*y;  
    z += bar(temp2);  
  }  
}
```


Lecture 3

- Review
- Blocks and Compound Statements
- **Control Flow**
 - Conditional Statements
 - Loops
- Functions
- Modular Programming
- Variable Scope
 - Static Variables
 - Register Variables

Control conditions

- Unlike C++ or Java, no *booleantype* (in C89/C90)
 - in C99, `bool` type available (use `stdbool.h`)
- Condition is an expression (or series of expressions)
e.g. `n<3` or `x<y || z<y`
- Expression is non-zero \Rightarrow condition true
- Expression must be numeric (or a pointer)

```
const char str[] = "some text";  
if (str) /* string is not null */  
    return 0;
```

Conditional statements

- The `if` statement
- The `switch` statement

The `if` statement

```
if (x% 2)  
  y += x/2;
```

- Evaluate condition
 `if (x %2==0)`
- If true, evaluate inner statement
 `y += x/2;`
- Otherwise, do nothing

The `else` keyword

```
if (x%2 == 0)
    y += x/2;
else
    y += (x+1)/2;
```

- Optional
- Execute statement if condition is false
y += (x+1)/2;
- Either inner statement may be block

The `else if` keyword

```
if (x%2 == 0)
    y += x/2;
else if (x%4 == 1)
    y += 2*((x+3)/4);
else
    y += (x+1)/2;
```

- Additional alternative control paths
- Conditions evaluated in order until one is met; inner statement then executed
- If multiple conditions true, only first executed
- Equivalent to nested `if` statements

Nesting `if` statements

```
if (x%4 == 0)
    if (x%2 == 0)
        y = 2;
else
    y = 1;
```

To which `if` statement does the `else` keyword belong?

Nesting `if` statements

To associate `else` with outer `if` statement: use braces

```
if (x%4 == 0) {  
    if (x%2 == 0)  
        y = 2;  
} else  
    y = 1;
```


The switch statement

- Alternative conditional statement
- Integer (or character) variable as input
- Considers cases for value of variable

```
switch (ch) {  
    case 'Y' : /* ch == 'Y' */  
        /* do something */  
        break ;  
    case 'N' : /* ch == 'N' */  
        /* do something else */  
        break ;  
    default : /* otherwise */  
        /* do a third thing */  
        break ;  
}
```

Multiple cases

- Compares variable to each case in order
- When match found, starts executing inner code until `break;` reached
- Execution “falls through” if `break;` not included

```
switch (ch) {
  case 'Y':
  case 'y':
    /* do something if
       ch == 'Y' or
       ch == 'y' */
    break ;
}

switch (ch) {
  case 'Y':
    /* do something if
       ch == 'Y' */
  case 'N':
    /* do something if
       ch == 'Y' or
       ch == 'N' */
    break ;
}
```

The `switch` statement

- Contents of `switch` statement a block
- Case labels: different entry points into block
- Similar to labels used with `goto` keyword (next lecture. . .)

Loop statements

- The `while` loop
- The `for` loop
- The `do-while` loop
- The `break` and `continue` keywords

The while loop

```
while (/ * condition   */  
/* loop body */
```

- Simplest loop structure – evaluate body as long as condition is true
- Condition evaluated first, so body may never be executed

The for loop

```
int factorial ( int n) {  
    int i , j =1;  
    for (i =1; i <= n; i++)  
        j *= i;  
    return j;  
}
```

- The “counting” loop
- Inside parentheses, three expressions, separated by semicolons:
 - Initialization: `i=1`
 - Condition: `i <= n`
 - Increment: `i++`
- Expressions can be empty (condition assumed to be “true”)

The for loop

Equivalent to `while` loop:

```
int factorial ( int n) {  
    int j =1;  
    int i =1; /* initialization */  
    while (i <= n /* condition */) {  
        j *= i;  
        i++; /* increment */  
    }  
    return j;  
}
```

The `for` loop

- Compound expressions separated by commas

```
int factorial ( int n) {  
    int i, j;  
    for (i =1, j =1; i <= n; j *= i, i++)  
        ;  
    return j;  
}
```

- Comma: operator with lowest precedence, evaluated left-to-right; not same as between function arguments

The do-while loop

```
char c;
do {
    /* loop body */
    puts ( "Keep going? (y/n) " );
    c = getchar();
    /* other processing */
} while (c == 'y' && /* other conditions */);
```

- Differs from `while` loop – condition evaluated after each iteration
- Body executed at least once
- Note semicolon at end

The `break` keyword

- Sometimes want to terminate a loop early
- `break`; exits innermost loop or `switch` statement to exit early
- Consider the modification of the `do-while` example:

```
char c;
do {
    /* loop body */
    puts( "Keep going? (y/n) ");
    c = getchar();
    if (c != 'y')
        break;
    /* other processing */
} while ( /* other conditions */ );
```

The `continue` keyword

- Use to skip an iteration
- **continue**; skips rest of innermost loop body, jumping to loop condition
- Example:

```
#define min(a,b) ((a) < (b) ? (a) : (b))
```

```
int gcd(int a, int b) {  
    int i, ret = 1, minval = min(a,b);  
    for (i = 2; i <= minval; i++) {  
        if (a%i != 0) /* i not divisor of a */  
            continue ;  
        if (b%i == 0) /* i is divisor of both a and b */  
            ret = i;  
    }  
    return ret;  
}
```

Lecture 3

- Review
- Blocks and Compound Statements
- Control Flow
 - Conditional Statements
 - Loops
- **Functions**
- Modular Programming
- Variable Scope
 - Static Variables
 - Register Variables

Functions

- Already seen some functions, including `main()`:

```
int main ( void ) {  
    /* do stuff */  
    return 0; /* success */  
}
```

- Basic syntax of functions explained in Lecture 1
- How to write a program using functions?

Divide and conquer

- Conceptualize how a program can be broken into smaller parts
- Let's design a program to solve linear Diophantine equation ($ax + by = c, x, y$: integers):

get a, b, c from command line

compute $g = \text{gcd}(a, b)$

if (c is not a multiple of the gcd)

no solutions exist; exit

run Extended Euclidean algorithm on a, b

rescale x and y output by (c/g)

print solution

- Extended Euclidean algorithm: finds integers x, y s.t.

$$ax + by = \text{gcd}(ab).$$

Computing the gcd

- Compute the gcd using the Euclidean algorithm:

```
int gcd ( int a, int b) {  
    while (b) { /* if a < b, performs swap */  
        int temp = b;  
        b = a%b;  
        a = temp ;  
    }  
    return a;  
}
```

- Algorithm relies on $\gcd(ab) = \gcd(ba \bmod b)$, for natural numbers $a > b$.

[Knuth, D. E. The Art of Computer Programming, Volume 1: Fundamental Algorithms. 3rd ed. Addison-Wesley, 1997.]

Extended Euclidean algorithm

Pseudocode for Extended Euclidean algorithm:

```
Initialize state variables (x, y)  
if (a < b)  
    swap(a, b)  
while (b > 0) {  
    compute quotient, remainder  
    update state variables (x, y)  
}  
return gcd and state variables (x, y)
```

[Menezes, A. J., et al. Handbook of Applied Cryptography. CRC Press, 1996.]

Returning multiple values

- Extended Euclidean algorithm returns gcd, and two other state variables, x and y
- Functions only return (up to) one value
- Solution: use *global* variables
- Declare variables for other outputs outside the function
 - variables declared outside of a function block are globals
 - persist throughout life of program
 - can be accessed/modified in any function

Divide and conquer

- Break down problem into simpler sub-problems
- Consider iteration and recursion
 - How can we implement $\text{gcd}(a,b)$ recursively?
- Minimize transfer of state between functions
- Writing pseudocode first can help

6.087 Lecture 3 – January 13, 2010

- Review
- Blocks and Compound Statements
- Control Flow
 - Conditional Statements
 - Loops
- Functions
- **Modular Programming**
- Variable Scope
 - Static Variables
 - Register Variables

Programming modules in C

- C programs do not need to be monolithic
- Module: interface and implementation
 - interface: header files
 - implementation: auxiliary source/object files
- Same concept carries over to external libraries (next week. . .)

The Euclid module

- Euclid's algorithms useful in many contexts
- Would like to include functionality in many programs
- Solution: make a module for Euclid's algorithms
- Need to write header file (.h) and source file (.c)

The source: euclid.c

Implement `gcd()` in `euclid.c`:

```
/* The gcd() function */
int gcd(int a, int b) {
    while (b) { /* if a < b, performs swap */
        int temp = b;
        b = a%b;
        a = temp;
    }
    return a;
}
```

Extended Euclidean algorithm implemented as `ext_euclid()`, also in `euclid.c`

The `extern` keyword

- Need to inform other source files about functions/global variables in `euclid.c`
- For functions: put function prototypes in a header file
- For variables: re-declare the global variable using the `extern` keyword in header file
- `extern` informs compiler that variable defined somewhere else
- Enables access/modifying of global variable from other source files

The header: euclid.h

Header contains prototypes for `gcd()` and `ext_euclid()`:

```
/* ensure included only once */
#ifndef __EUCLID_H__
#define __EUCLID_H__

/* global variables (declared in euclid.c) */
extern int x, y;

/* compute gcd */
int gcd (int a, int b);

/* compute  $g = \text{gcd}(a,b)$  and solve  $ax+by=g$  */
int ext_euclid (int a, int b);

#endif
```


Using the Euclid module

- Want to be able to call `gcd()` or `ext_euclid()` from the main file `diophant.c`
- Need to include the header file `euclid.h`:
`#include "euclid.h"` (file in `."`, not search path)
- Then, can call as any other function:

```
/* compute g = gcd(a,b) */  
g = gcd(a,b);
```

```
/* compute x and y using Extended Euclidean alg. */  
g = ext_euclid(a,b);
```

- Results in global variables `x` and `y`

```
/* rescale so ax+by = c */  
grow = c/g;  
x *= grow;  
y *= grow;
```

Compiling with the Euclid module

- Just compiling `diophant.c` is insufficient
- The functions `gcd()` and `ext_euclid()` are defined in `euclid.c`; this source file needs to be compiled, too
- When compiling the source files, the outputs need to be linked together into a single output
- One call to `gcc` can accomplish all this:

```
prompt% gcc -g -O0 -Wall diophant.c
euclid.c -o diophant.exe
```
- `diophant.exe` can be run as usual

Lecture 3

- Review
- Blocks and Compound Statements
- Control Flow
 - Conditional Statements
 - Loops
- Functions
- Modular Programming
- **Variable Scope**
 - Static Variables
 - Register Variables

Variable scope

- *scope* – the region in which a variable is valid
- Many cases, corresponds to block with variable's declaration
- Variables declared outside of a function have global scope
- Function definitions also have scope

An example

What is the scope of each variable in this example?

```
int nmax = 20;

/* The main() function */
int main ( int argc , char ** argv) /* entry point */
{
    int a=0, b=1, c, n;
    printf ( "%3d: %d\n" ,1 ,a);
    printf ( "%3d: %d\n" ,2 ,b);
    for (n=3; n<= nmax; n++) {
        c =a+b; a=b; b=c;
        printf ( "%3d: %d\n" ,n, c);
    }
    return 0; /* success */
}
```

Scope and nested declarations

How many lines are printed now?

```
int nmax = 20;

/* The main() function */
int main ( int argc , char ** argv) /* entry point */
{
    int a=0, b=1, c, n, nmax =25;
    printf ( "%3d: %d\n" ,1 ,a );
    printf ( "%3d: %d\n" ,2 ,b );
    for (n =3; n<= nmax; n++) {
        c =a+b; a=b; b=c;
        printf ( "%3d: %d\n" ,n, c );
    }
    return 0; /* success */
}
```

Static variables

- `static` keyword has two meanings, depending on where the static variable is declared
- Outside a function, `static` variables/functions only visible within that file, not globally (cannot be `extern`'ed)
- Inside a function, `static` variables:
 - are still local to that function
 - are initialized only during program initialization
 - do not get reinitialized with each function call

```
static  int  somePersistentVar    = 0;
```

Register variables

- During execution, data processed in *registers*
- Explicitly store commonly used data in registers – minimize load/store overhead
- Can explicitly declare certain variables as registers using `register` keyword
 - must be a simple type (implementation-dependent)
 - only local variables and function arguments eligible
 - excess/unallowed register declarations ignored, compiled as regular variables
- Registers do not reside in addressed memory; pointer of a register variable illegal

Example

Variable scope example, revisited, with `register` variables:

```
/* The main() function */
int main ( register int argc , register char ** argv )
{
    register int a=0, b=1, c, n, nmax =20;
    printf ( "%3d: %d\n" ,1 ,a );
    printf ( "%3d: %d\n" ,2 ,b );
    for (n=3; n<= nmax; n++) {
        c =a+b; a=b; b=c;
        printf ( "%3d: %d\n" ,n, c );
    }
    return 0; /* success */
}
```

Summary

Topics covered:

- Controlling program flow using conditional statements and loops
- Dividing a complex program into many simpler sub-programs using functions and modular programming techniques
- Variable scope rules and `extern`, `static`, and `register` variables

MIT OpenCourseWare
<http://ocw.mit.edu>

6.087 Practical Programming in C

January (IAP) 2010

For information about citing these materials or our Terms of Use, visit: <http://ocw.mit.edu/terms>.